



MATERIAL SAFETY DATA SHEET

Unleaded Gasoline

VALERO MARKETING & SUPPLY COMPANY
and Affiliates
P.O. Box 696000
San Antonio, TX 78269-6000

Emergency Phone Numbers

24 Hour Emergency: 866-565-5220
Chemtrec Emergency: 800-424-9300

General Assistance

General Assistance: 210-345-4593

BRAND NAMES: Valero, Diamond Shamrock, Shamrock, Ultramar, Beacon, Total

Section 1. Chemical Product and Company Identification

Common / Trade name : Unleaded Gasoline

Synonym : Regular/Premium/Midgrade - Unleaded Gasoline, Petrol, Motor Fuel, Reformulated Gasoline, RFG, Conventional, Oxygenated, Non-Oxygenated, CARB Gasoline

SYNONYMS/COMMON NAMES: This Material Safety Data Sheet applies to the listed products and synonym descriptions for Hazard Communication purposes only. Technical specifications vary greatly depending on the product and are not reflected in this document. Consult specification sheets for technical information. This product contains ingredients that are considered to be hazardous as defined by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Material uses : Motor fuels.

MSDS# : 002

CAS # : 86290-81-5

Section 2. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>Concentration (%)</u>
Gasoline	86290-81-5	0 - 100
Hexane (Other Isomers)	mixture	5 - 25
Toluene	108-88-3	0 - 30
Xylene (o,m,p isomers)	1330-20-7	0 - 25
Octane (All Isomers)	111-65-9	0 - 18.5
Methyl Tertiary Butyl Ether (MTBE)	1634-04-4	0 - 16
Ethanol	64-17-5	0 - 10
1,2,4-Trimethylbenzene	95-63-6	0 - 6
n-Heptane	142-82-5	1 - 5
Pentane	109-66-0	1 - 5
Tertiary Amyl Methyl Ether (TAME)	994-05-8	0 - 6
Ethylbenzene	100-41-4	0 - 5
Cumene	98-82-8	0 - 5
Benzene	71-43-2	0 - 4.9
Cyclohexane	110-82-7	0 - 3
n-Hexane	110-54-3	0 - 3

Continued on next page

Section 3. Hazards Identification

Danger! Contains Benzene. Cancer Hazard. Can cause kidney, liver and blood disorders. May cause irritation to eyes, skin and respiratory system. Avoid liquid, mist and vapor contact. Harmful or fatal if swallowed. Aspiration hazard; can enter lungs and cause damage. May cause irritation or be harmful if inhaled or absorbed through the skin. Extremely flammable liquid. Vapors may explode.

- Physical state** : Liquid.
- Emergency overview** : Warning!
CANCER HAZARD
CONTAINS MATERIAL WHICH CAN CAUSE CANCER
HIGHLY FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF SWALLOWED.
CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:
BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, PERIPHERAL
NERVOUS SYSTEM, GASTROINTESTINAL TRACT, RESPIRATORY TRACT, SKIN,
BONE MARROW, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.
VAPOR MAY CAUSE FLASH FIRE.
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.
 Do not ingest. Avoid prolonged contact with eyes, skin, and clothing. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Risk of cancer depends on duration and level of exposure.
- Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.
- Potential acute health effects**
- Eyes** : May cause severe irritation, redness, tearing, blurred vision and conjunctivitis.
- Skin** : Prolonged or repeated contact may cause moderate irritation, defatting (cracking), redness, itching, inflammation, dermatitis and possible secondary infection. High pressure skin injections are **SERIOUS MEDICAL EMERGENCIES**. Injury may not appear serious at first. Within a few hours, tissues will become swollen, discolored and extremely painful.
- Inhalation** : Nasal and respiratory tract irritation, central nervous system effects including excitation, euphoria, contracted eye pupils, dizziness, drowsiness, blurred vision, fatigue, nausea, headache, loss of reflexes, tremors, convulsions, seizures, loss of consciousness, coma, respiratory arrest and sudden death could occur as a result of long term and/or high concentration exposure to vapors. May also cause anemia and irregular heart rhythm. Repeated or prolonged exposure may cause behavioral changes.
- Ingestion** : Toxic if swallowed. This product may be harmful or fatal if swallowed. This product may cause nausea, vomiting, diarrhea and restlessness. **DO NOT INDUCE VOMITING**. Aspiration into the lungs can cause severe chemical pneumonitis or pulmonary edema/hemorrhage, which can be fatal. May cause gastrointestinal disturbances. Symptoms may include irritation, depression, vomiting and diarrhea. May cause harmful central nervous system effects, similar to those listed under "inhalation".
- Medical conditions aggravated by overexposure:** : Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs. Preexisting eye, skin, heart, central nervous system and respiratory disorders may be aggravated by exposure to this product. Impaired kidney, liver and blood disorders may be aggravated by exposure to this product.
- Over-exposure signs/symptoms** : Nasal and respiratory tract irritation, central nervous system effects including excitation, euphoria, contracted eye pupils, dizziness, drowsiness, blurred vision, fatigue, nausea, headache, loss of reflexes, tremors, convulsions, seizures, loss of consciousness, coma, respiratory arrest or sudden death could occur as a result of long term and/or high concentration exposure to vapors. May also cause anemia and irregular heart rhythm.

See toxicological Information (section 11)

Section 4. First Aid Measures

- Eye contact** : Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Seek medical advice if pain or redness continues.
- Skin contact** : Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water. Remove contaminated clothing promptly and launder before reuse. Contaminated leather goods should be discarded. If irritation persists or symptoms described in the MSDS develop, seek medical attention. High pressure skin injections are SERIOUS MEDICAL EMERGENCIES. Get immediate medical attention.
- Inhalation** : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
- Ingestion** : This product may be harmful or fatal if swallowed. This product may cause nausea, vomiting, diarrhea and restlessness. DO NOT INDUCE VOMITING. Aspiration into the lungs can cause severe chemical pneumonitis or pulmonary edema/hemorrhage, which can be fatal. May cause gastrointestinal disturbances. Symptoms may include irritation, depression, vomiting and diarrhea. May cause harmful central nervous system effects, similar to those listed under "inhalation".
- Notes to physician** : In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption. Consideration should be given to the use of an intratracheal tube, to prevent aspiration. Irregular heart beat may occur, use of adrenalin is not advisable. Individuals intoxicated by the product should be hospitalized immediately, with acute and continuing attention to neurological and cardiopulmonary function. Positive pressure ventilation may be necessary. After the initial episode, individuals should be monitored for changes in blood variables and the delayed appearance of pulmonary edema and chemical pneumonitis. Such patients should be monitored for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment. Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated. In case of skin injection, prompt debridement of the wound is necessary to minimize necrosis and tissue loss.

Section 5. Fire Fighting Measures

- Flammability of the product** : Flammable.
- Auto-ignition temperature** : >260°C (500°F)
- Flash point** : Closed cup: -40°C (-40°F).
- Flammable limits** : Lower: 1.3% Upper: 7.1%
- Products of combustion** : These products are carbon oxides (CO, CO₂), nitrogen and sulfur oxides (NO_x, SO_x), particulate matter, VOC's.
- Fire hazards in presence of various substances** : Extremely flammable in presence of open flames, sparks and static discharge.
- Explosion hazards in presence of various substances** : Explosive in presence of open flames, sparks and static discharge.
- Fire fighting media and instructions** : Flammable Liquid. Use dry chemical, foam or carbon dioxide to extinguish the fire. Consult foam manufacturer for appropriate media, application rates and water/foam ratio. Subsurface application is only recommended where it is known that the fuel contains less than 3% oxygenated blending components. Water can be used to cool fire- exposed containers, structures and to protect personnel. If a leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water to flush spills away from sources of ignition. Do not flush down public sewers.
- Collect contaminated fire fighting water separately. It must not enter the sewage system. Dike area of fire to prevent product run-off. Decontaminate emergency personnel and equipment with soap and water.

Special protective equipment for fire-fighters

Highly flammable liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

: Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Special remarks on fire hazards

: Dangerous when exposed to heat or flame. Vapors form flammable or explosive mixtures with air at room temperature. Vapor or gas may spread to distant ignition sources (pilot lights, welding equipment, electrical equipment, etc.) and flash back. Vapors may accumulate in low areas. Vapors may concentrate in confined areas. Flowing product can be ignited by self generated static electricity. Use adequate bonding and grounding to prevent static buildup. Runoff to sewer may cause fire or explosion hazard. Containers may explode in heat of fire. Irritating or toxic substances may be emitted upon thermal decomposition. For fires involving this material, do not enter any enclosed or confined space without proper protective equipment, which may include NIOSH approved self-contained breathing apparatus with full face mask. Clothing, rags or similar organic material contaminated with this product and stored in a closed space may undergo spontaneous combustion. Transfer to and from commonly bonded and grounded containers.

Special remarks on explosion hazards

: No additional remark.

Section 6. Accidental Release Measures**Personal precautions**

: Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material. Tanks, vessels or other confined spaces which have contained product should be freed of vapors before entering. The container should be checked to ensure a safe atmosphere before entry. Empty containers may contain toxic, flammable/combustible or explosive residues or vapors. Do not cut, grind, drill, weld or reuse empty containers that contained this product. Do not transfer this product to another container unless the container receiving the product is labeled with proper DOT shipping name, hazard class and other information that describes the product and its hazards.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Gasoline may contain oxygenated blend products (Ethanol, MTBE, etc.) that are soluble in water and therefore precautions should be taken to protect surface and groundwater sources from contamination. If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Extremely flammable. Review Fire and Explosion Hazard Data before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g., by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, contact the National Response Center at 800-424- 8802. For highway or railway spills, contact Chemtrec at 800-424-9300.

Methods for cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and Storage

Handling : Do not ingest. Avoid prolonged contact with eyes, skin, and clothing. Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling. Use only in well ventilated locations. Keep away from heat, spark and flames. In case of fire, use water spray, foam, dry chemical or carbon dioxide as described in the Fire and Explosion Hazard Data section of the MSDS. Do not pressurize, cut, weld, braze, solder, drill on or near this container. "Empty" container contains residue (liquid and/or vapor) and may explode in heat of a fire.

Keep out of reach of children. Failure to use caution may cause serious injury or illness. Never siphon by mouth. For use as a motor fuel only. Do not use as a cleaning solvent or for other non-motor fuel uses. To prevent ingestion and exposure - Do not siphon by mouth to transfer product between containers. Use good personal hygiene practices. After handling this product, wash hands before eating, drinking, or using toilet facilities.

Storage : Store in tightly closed containers in cool, dry, isolated and well ventilated area away from heat, sources of ignition and incompatible materials. Use non-sparking tools and explosion proof equipment. Ground lines, containers, and other equipment used during product transfer to reduce the possibility of a static induced spark. Do not "switch load" because of possible accumulation of a static charge resulting in a source of ignition. Use good personal hygiene practices. After handling this product, wash hands before eating, drinking, smoking or using toilet facilities.

Section 8. Exposure Controls, Personal Protection

Engineering controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal protection

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Keep away from eyes. Eye contact can be avoided by wearing safety glasses or chemical splash goggles.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Keep away from skin. Skin contact can be minimized by wearing protective gloves such as neoprene, nitrile-butadiene rubber, etc. and, where necessary, impervious clothing and boots. Leather goods contaminated with this product should be discarded. A source of clean water should be available in the work area for flushing eyes and skin. Flame Retardant Clothing is recommended.

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workplace exposure limits for product or components are exceeded, NIOSH approved equipment should be worn. Proper respirator selection should be determined by adequately trained personnel, based on the contaminants, the degree of potential exposure and published respiratory protection factors. This equipment should be available for nonroutine and emergency use.

Hands : Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Personal protective equipment (Pictograms) : Consult your Supervisor or S.O.P. for special handling directions.



Personal protection in case of a large spill : Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Component

Exposure limits

Gasoline

ACGIH TLV (United States, 5/2004).

STEL: 500 ppm 15 minute(s). Form: All forms

TWA: 300 ppm 8 hour(s). Form: All forms

Hexane (Other Isomers)

ACGIH TLV (United States, 9/2004).

STEL: 1000 ppm 15 minute(s). Form: All forms

TWA: 500 ppm 8 hour(s). Form: All forms

Toluene

NIOSH REL (United States, 6/2001).

CEIL: 510 ppm 15 minute(s). Form: All forms

ACGIH TLV (United States, 5/2004). Skin Notes: 1996 Adoption Refers to Appendix A – Carcinogens.

TWA: 50 ppm 8 hour(s). Form: All forms

NIOSH REL (United States, 6/2001).

STEL: 150 ppm 15 minute(s). Form: All forms

TWA: 100 ppm 10 hour(s). Form: All forms

OSHA PEL Z2 (United States, 6/2002).

AMP: 500 ppm 10 minute(s). Form: All forms

CEIL: 300 ppm Form: All forms

TWA: 200 ppm 8 hour(s). Form: All forms

Xylene (o,m,p isomers)

ACGIH TLV (United States, 5/2004).

STEL: 150 ppm 15 minute(s). Form: All forms

TWA: 100 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 6/1993).

TWA: 100 ppm 8 hour(s). Form: All forms

Octane (All Isomers)

NIOSH REL (United States, 6/2001).

CEIL: 385 ppm 15 minute(s). Form: All forms

TWA: 75 ppm 10 hour(s). Form: All forms

OSHA PEL (United States, 6/1993).

TWA: 500 ppm 8 hour(s). Form: All forms

ACGIH TLV (United States, 3/2004). Notes: 1999 Adoption.

TWA: 300 ppm 8 hour(s). Form: All forms

Methyl Tertiary Butyl Ether (MTBE)

ACGIH TLV (United States, 1/2004). Notes: 2002 Adoption.

TWA: 50 ppm 8 hour(s). Form: All forms

Ethanol

ACGIH TLV (United States, 5/2004). Notes: 1996 Adoption Refers to Appendix A – Carcinogens.

TWA: 1000 ppm 8 hour(s). Form: All forms

NIOSH REL (United States, 6/2001).

TWA: 1000 ppm 10 hour(s). Form: All forms

OSHA PEL (United States, 6/1993).

TWA: 1000 ppm 8 hour(s). Form: All forms

1,2,4-Trimethylbenzene

NIOSH REL (United States, 6/2001).

TWA: 25 ppm 10 hour(s). Form: All forms

n-Heptane

ACGIH TLV (United States, 9/2004).

STEL: 500 ppm 15 minute(s). Form: All forms

TWA: 400 ppm 8 hour(s). Form: All forms

NIOSH REL (United States, 6/2001).

TWA: 350 mg/m³ 10 hour(s). Form: All forms

OSHA PEL (United States, 6/1993).

TWA: 500 ppm 8 hour(s). Form: All forms

Pentane

ACGIH TLV (United States, 9/2004). Notes: 1998 Adoption.

TWA: 600 ppm 8 hour(s). Form: All forms

	TWA: 600 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). CEIL: 610 ppm 15 minute(s). Form: All forms TWA: 120 ppm 10 hour(s). Form: All forms OSHA PEL (United States, 6/1993). TWA: 1000 ppm 8 hour(s). Form: All forms ACGIH TLV (United States, 1/2004). Notes: 2002 Adoption. TWA: 20 ppm 8 hour(s). Form: All forms
Tertiary Amyl Methyl Ether (TAME)	ACGIH TLV (United States, 1/2004). STEL: 125 ppm 15 minute(s). Form: All forms TWA: 100 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). STEL: 125 ppm 15 minute(s). Form: All forms TWA: 100 ppm 10 hour(s). Form: All forms OSHA PEL (United States, 6/1993). TWA: 100 ppm 8 hour(s). Form: All forms
Ethylbenzene	ACGIH TLV (United States, 1/2004). TWA: 50 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). Notes: 1999 Adoption. TWA: 50 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). Skin TWA: 50 ppm 10 hour(s). Form: All forms OSHA PEL (United States, 6/1993). Skin TWA: 50 ppm 8 hour(s). Form: All forms
Cumene	NIOSH REL (United States, 6/2001). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen STEL: 1 ppm 15 minute(s). Form: All forms TWA: 0.1 ppm 10 hour(s). Form: All forms ACGIH TLV (United States, 5/2004). Skin STEL: 2.5 ppm 15 minute(s). Form: All forms TWA: 0.5 ppm 8 hour(s). Form: All forms OSHA PEL (United States, 6/1993). STEL: 5 ppm 15 minute(s). Form: All forms TWA: 1 ppm 8 hour(s). Form: All forms
Benzene	ACGIH TLV (United States, 1/2004). TWA: 100 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). TWA: 300 ppm 10 hour(s). Form: All forms OSHA PEL (United States, 6/1993). TWA: 300 ppm 8 hour(s). Form: All forms OSHA PEL (United States, 6/1993). TWA: 500 ppm 8 hour(s). Form: All forms ACGIH TLV (United States, 9/2004). Skin TWA: 50 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). TWA: 50 ppm 10 hour(s). Form: All forms
Cyclohexane	
n-Hexane	

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

Physical state	: Liquid.
Color	: Light Straw to Red Clear Liquid
Odor	: Characteristic Gasoline Odor (Strong.)
Boiling point	: 26.7 to 226.7°C (80.1 to 440.1°F)
Melting/freezing point	: May start to solidify at 6.67°C (44°F) based on data for: Cyclohexane. Weighted average: -91.9°C (-133.4°F)
Specific gravity	: 0.66 to 0.75 (Water = 1) (@ 60 °F)
Vapor pressure	: 60.8 to 101.3 kPa (456 to 760 mm Hg) (at 20°C)
Vapor density	: 3 to 4 (Air = 1)
Volatility	: Essentially 100%

Continued on next page

- Evaporation rate** : 10 to 11 compared to Butyl acetate.
- Solubility** : Very slightly soluble in cold water, hot water.

Section 10. Stability and Reactivity Data

- Stability and reactivity** : The product is stable.
- Incompatibility with various substances** : Reactive with oxidizing agents, reducing agents, acids, alkalis.
- Hazardous decomposition products** : These products are carbon oxides (CO, CO₂), nitrogen and sulfur oxides (NO_x, SO_x), particulate matter, VOC's.
- Hazardous polymerization** : Will not occur.

Section 11. Toxicological Information

Toxicity data

BENZENE is considered to be a carcinogen to humans, and may cause adverse health effects following exposure via inhalation, ingestion or dermal or eye contact. Acute inhalation of benzene by rats, mice or rabbits caused narcosis, spontaneous heart contractions (ventricular fibrillation) and death due to respiratory paralysis. Subchronic inhalation of benzene by rats produced decreased white blood cell counts, decreased bone marrow cell activity, increased red blood cell activity and cataracts. In rats, chronic inhalation or oral administration of benzene produced cancers of the liver, mouth and Zymbal gland. Acute inhalation exposure of benzene in humans has caused nerve inflammation (polyneuritis), central nervous system depression and cardiac sensitization. Chronic exposure to benzene has produced anorexia and irreversible injury to the blood forming organs. Potential effects include aplastic anemia and leukemia. It has caused fetal defects in tests on laboratory animals.

CUMENE can affect the body if it is inhaled, swallowed or comes in contact with the eyes or skin. The main toxic effect is irritation of the eyes, skin and upper respiratory tract. Narcosis has been reported to occur in animals on high exposure. There are no reports of systemic effects in man as a result of industrial exposure. Chronic exposure of rats above 500 ppm causes congestion of lungs, liver and kidneys, but no bone marrow changes.

CYCLOHEXANE can affect the body if it is inhaled, swallowed, or comes in contact with the eyes or skin. It is primarily a local irritant and central nervous system depressant. The depressant effect is from exposure to concentrations above 12,000 ppm, while prolonged or repeated exposure to concentrations above 300 ppm produces a mild irritation of the eyes and upper respiratory tract.

ETHANOL is rapidly absorbed through the gastrointestinal tract and normally metabolized and excreted in a relatively few hours. Only in very unusual work situations could the inhalation of ethanol vapors result in symptoms of alcohol intoxication. Can be fatal or cause blindness if swallowed in extreme quantities. Inhalation or ingestion can cause headache, nausea, dizziness or narcosis. Chronic overexposure (inhalation or ingestion) can cause damage to the gastrointestinal tract, liver, kidneys and cardiovascular system. Prolonged contact causes irritation to skin and eyes. Medical conditions aggravated by exposure include kidney, liver, heart and GI conditions. This material is not listed as a cancer causing agent but is suspected of being a promoter.

ETHYLBENZENE can affect the body if it is inhaled, swallowed or comes in contact with the eyes or skin. It is primarily an irritant of skin, and to some degree, of eyes and upper respiratory tract. Systemic absorption causes depression of the central nervous system with narcosis at very high concentrations. On the eyes and nose, the vapor at 5000 ppm causes intolerable irritation, eye irritation and lacrimation are immediate and severe at 2000 ppm, irritation and tearing occur at 1000 ppm although tolerance develops rapidly, and the vapor is a transient irritant on human eyes at 200 ppm. Aspiration of small amounts causes extensive edema and hemorrhage of lung tissue. A draft report on a study conducted by the National Toxicology program states that lifetime inhalation exposure of rats and mice to concentrations of ethylbenzene(750 ppm) resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations of ethylbenzene (75 ppm or 250 ppm). The draft report does not address the relevance of these results to humans.

GASOLINE contains benzene, as well as n-hexane, other aromatics and certain olefins. Gasoline generally acts as an anesthetic and mucous membrane irritant. Inhalation is the most important route of occupational entry. Eye and throat irritation occur in several hours at exposures of 160 to 270 ppm, eye, nose and throat irritation and dizziness occurs at exposures of 500 to 900 ppm in one hour, mild anesthesia occurs in 30 minutes at exposures of 2000 ppm. The threshold for immediate mild toxic effect is 900 to 1000 ppm. There are reports of toxic neuritis after exposure to gasoline. Repeated exposure of laboratory animals to high concentrations of gasoline vapors has caused kidney damage and cancer in rats and cancer in mice. Gasoline was evaluated for genetic activity in assays using microbial cells, cultured mammalian cells and rat bone marrow cells. The results were all negative so gasoline was considered nonmutagenic under these conditions. Overexposure to this product or its components has been suggested as a cause of liver abnormalities in laboratory animals and humans. Lifetime studies by the American Petroleum Institute have shown that kidney damage and kidney cancer can occur in male rats after prolonged inhalation exposures at elevated concentrations of total gasoline. Kidneys of mice and female rats were unaffected. The U.S. EPA Risk Assessment Forum has concluded that the male rat kidney tumor results are not relevant for humans. Total gasoline exposure also produced liver tumors in female mice only. The implication of these data for humans has not been determined.

HEPTANE can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. Heptane vapor is a narcotic. Concentrations of 10,000 to 15,000 ppm produced narcosis in mice within 30 to 60 minutes, while 15,000 to 20,000 ppm caused convulsions and death. At 48,000 ppm, respiratory arrest was produced in mice in 3 to 4 minutes from the start of exposure. Human subjects exposed to 1,000 ppm for 6 minutes, or to 2,000 ppm for 4 minutes, reported slight vertigo. At 5,000 ppm for 4 minutes, there was marked vertigo, inability to walk a straight line, hilarity, and incoordination, but no complaints of eye and upper respiratory tract or mucous membrane irritation. A 15-minute exposure at 5,000 ppm produced in some subjects a state of stupor lasting for 30 minutes after exposure. These subjects also reported loss of appetite, slight nausea, and a taste resembling gasoline for several hours after exposure. Although chronic nervous system effects have not been attributed to heptane, polyneuritis has been reported following prolonged exposure to a petroleum fraction with boiling range between 70°C and 100° C, and this fraction would normally contain various isomers of heptane as major ingredients.

Continued on next page

n-HEXANE can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. Hexane vapor is a narcotic and a mild upper respiratory irritant. Polyneuropathy (peripheral nerve damage) has been reported to occur in workers exposed to hexane vapors, characterized by progressive weakness and numbness in the extremities, loss of deep tendon reflexes and reduction of motor nerve conduction velocity. Recovery ranges from no recovery to complete recovery depending upon the duration of exposure and severity of nerve damage. Concentrations of 30,000 ppm produced narcosis in mice within 30 to 60 minutes, convulsions and death occurred at 35,000 to 40,000 ppm, and at 64,000 ppm respiratory arrest was produced in 2.5 to 4.5 minutes from the start of exposure. Concentrations up to 8000 ppm produced no anesthesia. In human subjects, 2000 ppm for 10 minutes produced no effects, but 5000 ppm resulted in dizziness and a sensation of giddiness. Other investigators reported slight nausea, headache and irritation of the eyes and throat at 1400 to 1500 ppm. In industrial practice, mild narcotic symptoms such as dizziness have been observed when concentrations exceeded 1000 ppm, but not below 500 ppm.

MTBE is a mild irritant to the eye. An increase in anesthesia with increasing concentrations was observed during a rat exposure study. Controlled human exposure to MTBE in air under relatively temperate conditions does not cause increased symptoms or measurable responses (irritation, behavioral changes) in healthy adult subjects. Although MTBE and TBA were detectable in the blood of subjects in clinical studies, no increase in symptoms occurred. A tentative review of the carcinogenicity (i.e., a tentative C classification). A sensitivity analysis of cancer risk indices also suggests that, if MTBE is carcinogenic, its potency is not likely to be greater than that already assigned to gasoline itself, which currently has a hazard classification of "probable" human carcinogen.

OCTANE can affect the body if it is inhaled, comes in contact with the skin or eyes or is swallowed. Octane vapor is a mild narcotic and mucous membrane irritant. Concentrations of 6600 to 13,700 ppm produced narcosis in mice in 30 to 90 minutes, the fatal concentration for animals is near 13,500 ppm. No chronic systemic effects have been reported in humans.

PENTANE can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. The chief effects of inhalation are narcosis and irritation of the respiratory passages. Exposures of 90,000 to 120,000 ppm resulted in narcosis in animals in 5 to 6 minutes, 130,000 ppm was fatal with respiratory arrest occurring within 5 minutes of exposure. Pentane injected subcutaneously in rats produced temporary impairment of liver function and moderate neutropenia. While other aliphatic hydrocarbons produce drowsiness and mild irritation of the eyes and nose in human subjects, no symptoms resulted from exposure to pentane vapor for 10 minutes at 5000 ppm. Chronic exposure to high concentrations may lead to polyneuropathy (peripheral nerve damage), characterized by progressive weakness and numbness in the extremities, loss of deep tendon reflexes and reduction of motor nerve conduction velocity.

TOLUENE can affect the body if it is inhaled, comes in contact with the eyes or skin or it is swallowed. It may also enter the body through the skin. Toluene vapors cause narcosis. Controlled exposures of human subjects to 200 ppm for 8 hours produced mild fatigue, weakness, confusion, lacrimation and paresthesia. At 600 ppm for 8 hours, there was euphoria, headache, dizziness, dilated pupils and nausea. At 800 ppm for 8 hours, symptoms were more pronounced, and after effects included nervousness, muscular fatigue and insomnia persisting for several days. In workers exposed for many years to concentrations in the range of 80 to 300 ppm, there was no clinical or laboratory evidence of altered liver function. Toluene exposure does not result in the same chronic injury to bone marrow caused by benzene. Liquid splashed in the eyes of workers has caused transient corneal damage and conjunctival irritation, complete recovery occurred within 48 hours. Animal studies have shown that inhalation of high levels of toluene produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms. This later effect was shown to be enhanced by hypoxia or the injection of adrenalin-like agents. Workers exposed at less than 200 ppm have complained of headache, lassitude and nausea, but physical findings were essentially negative. At concentrations between 200 and 500 ppm, impairment of coordination, momentary loss of memory and anorexia were present. Between 500 and 1500 ppm, palpitation, extreme weakness, pronounced loss of coordination and impairment of reaction time were noted. The red cell count fell in many instances and there were cases of aplastic anemia in which recovery followed intensive hospital treatment (although some of the effects may have been due to benzene impurity). Toluene has been reported to decrease immunological responses and cause recordable hearing loss in test animals. Damages genetic material in mammalian test systems. May cause adverse reproductive effects based on animal testing.

TRIMETHYL BENZENE (PSEUDOCUMENE) can affect the body if it is inhaled, comes in contact with the eyes or skin or it is swallowed. It may also enter the body through the skin. The liquid is a primary skin irritant, but system intoxication due to absorption through the skin is not probable. High concentrations of vapors (5000 to 9000 ppm) caused central nervous system depression. Pseudocumene may cause nervousness, tension, anxiety, and asthmatic bronchitis. In addition, the peripheral blood showed a tendency to hypochromic anemia and a deviation from the normal in the coagulability of the blood.

XYLENE can affect the body if it is inhaled, comes in contact with the eyes or skin or it is swallowed. It may also enter the body through the skin. Xylene vapor irritates the eyes, mucous membranes and skin. At high concentrations it causes narcosis. In animals, xylene causes blood changes reflecting mild toxicity to the hematopoietic system. Laboratory animals exposed by various routes to high doses of xylene showed evidence of effects in the liver, kidneys, lungs, spleen, heart and adrenals. Rats exposed to xylene vapor during pregnancy showed embryo/fetotoxic effects. Mice exposed orally to doses producing maternal toxicity also showed embryo or fetotoxic effects. Laboratory rats exposed to high concentrations of toluene experienced recordable hearing loss. In humans, exposure to high concentrations can cause dizziness, excitement, drowsiness, incoordination and a staggering gait. Workers exposed to concentrations above 200 ppm complain of anorexia, nausea, vomiting and abdominal pain. Brief exposures of humans to 200 ppm caused irritation of the eyes, nose and throat. There are reports of reversible corneal vacuolation in workers exposed to xylene, or to xylene plus other volatile solvents.

HEXANE ISOMERS are three times as toxic to mice as is pentane. Narcosis was produced in mice within 30-60 minutes at concentrations of 30,000 ppm. In man, concentrations for 10 minutes at 2000 ppm produced no effects, but 5000 ppm caused dizziness and a sense of giddiness. Concentrations of 1400-1500 ppm produced slight nausea, headache, eye, and throat irritation.

<u>Ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Toluene	LD50	636 mg/kg	Oral	Rat
	LDLo	50 mg/kg	Oral	human
Xylene (o,m,p isomers)	LD50	4300 mg/kg	Oral	Rat
	LD50	2119 mg/kg	Oral	Mouse
	LD50	4300 mg/kg	Oral	Mammal
	LD50	>1700 mg/kg	Dermal	Rabbit
	LDLo	50 mg/kg	Oral	human

Continued on next page

Ethanol	LD50	7060 mg/kg	Oral	Rat
	LD50	6300 mg/kg	Oral	Rabbit
	LD50	3450 mg/kg	Oral	Mouse
	LDLo	1400 mg/kg	Oral	human
	LDLo	5500 mg/kg	Oral	Dog
Tertiary Amyl Methyl Ether (TAME)	LD50	1602 mg/kg	Oral	Rat
Pentane	LD50	400 mg/kg	Oral	Rat
Cumene	LD50	1400 mg/kg	Oral	Rat
	LD50	12750 mg/kg	Oral	Mouse
	LD50	3500 mg/kg	Oral	Rat
Ethylbenzene	LD50	930 mg/kg	Oral	Rat
Benzene	LD50	4700 mg/kg	Oral	Mouse
	LD50	5700 mg/kg	Oral	Mammal
	LD50	48 mg/kg	Dermal	Mouse
	LDLo	50 mg/kg	Oral	man
	LD50	12705 mg/kg	Oral	Rat
	LD50	813 mg/kg	Oral	Mouse
	LDLo	5500 mg/kg	Oral	Rabbit
Cyclohexane	LD50	12705 mg/kg	Oral	Rat
	LD50	813 mg/kg	Oral	Mouse
	LDLo	5500 mg/kg	Oral	Rabbit

Chronic effects on humans : **CARCINOGENIC EFFECTS:** Classified A3 (Proven for animal.) by ACGIH [Gasoline]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Toluene]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Xylene (o,m,p isomers)]. Classified A3 (Proven for animal.) by ACGIH [Methyl Tertiary Butyl Ether (MTBE)]. Classified 3 (Not classifiable for human.) by IARC [Methyl Tertiary Butyl Ether (MTBE)]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC [Ethylbenzene]. Classified A1 (Confirmed for human.) by ACGIH, 1 (Proven for human.) by IARC, 1 (Known To Be Human Carcinogens.) by NTP, + (Proven.) by OSHA, + (Proven.) by NIOSH [Benzene]. Contains material which causes damage to the following organs: blood, kidneys, lungs, the reproductive system, liver, peripheral nervous system, gastrointestinal tract, upper respiratory tract, skin, bone marrow, central nervous system (CNS), eye, lens or cornea.

Other toxic effects on humans : Extremely hazardous in case of ingestion.
Very hazardous in case of eye contact (irritant), .
Hazardous in case of skin contact (irritant).
Slightly hazardous in case of inhalation (lung irritant).

Special remarks on toxicity to animals : No additional remark.

Special remarks on chronic effects on humans : No additional remark.

Special remarks on other toxic effects on humans : No additional remark.

Specific effects

Carcinogenic effects : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

Target organs : Contains material which causes damage to the following organs: blood, kidneys, lungs, the reproductive system, liver, peripheral nervous system, gastrointestinal tract, upper respiratory tract, skin, bone marrow, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological Information

Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Toluene	Daphnia magna (EC50)	48 hour(s)	6 mg/l
	Daphnia magna (EC50)	48 hour(s)	6.56 mg/l
	Oncorhynchus mykiss (EC50)	48 hour(s)	6.78 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	5.8 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	6.78 mg/l
	Pimephales promelas (LC50)	96 hour(s)	12.6 mg/l
Xylene (o,m,p isomers)	Oncorhynchus mykiss (LC50)	96 hour(s)	3.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	8.2 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	8.6 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	12 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	13.3 mg/l
	Pimephales promelas (LC50)	96 hour(s)	13.4 mg/l
Methyl Tertiary Butyl Ether (MTBE)	Pimephales promelas (LC50)	96 hour(s)	672 mg/l
	Ethanol		
Ethanol	Daphnia magna (EC50)	48 hour(s)	2 mg/l
	Daphnia magna (EC50)	48 hour(s)	9.3 mg/l
	Daphnia magna (EC50)	48 hour(s)	>100 mg/l
	Pimephales promelas (LC50)	96 hour(s)	>100 mg/l
	Daphnia magna (LC50)	96 hour(s)	>100 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	13000 mg/l
1,2,4-Trimethylbenzene	Pimephales promelas (LC50)	96 hour(s)	7.72 mg/l
	Cumene		
Cumene	Daphnia magna (EC50)	48 hour(s)	10.6 mg/l
	Daphnia magna (EC50)	48 hour(s)	11.2 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	2.7 mg/l
	Poecilia reticulata (LC50)	96 hour(s)	5.1 mg/l
	Pimephales promelas (LC50)	96 hour(s)	6.32 mg/l
	Ethylbenzene	Daphnia magna (EC50)	48 hour(s)
Daphnia magna (EC50)		48 hour(s)	2.97 mg/l
Selenastrum capricornutum (EC50)		48 hour(s)	7.2 mg/l
Oncorhynchus mykiss (LC50)		96 hour(s)	4.2 mg/l
Pimephales promelas (LC50)		96 hour(s)	9.09 mg/l
Poecilia reticulata (LC50)		96 hour(s)	9.6 mg/l
Benzene	Daphnia magna (EC50)	48 hour(s)	9.23 mg/l
	Daphnia magna (EC50)	48 hour(s)	10 mg/l
	Daphnia magna (EC50)	48 hour(s)	11.73 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	5.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	5.9 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	9.2 mg/l
n-Hexane	Pimephales promelas (LC50)	96 hour(s)	2.5 mg/l
Cyclohexane	Pimephales promelas (LC50)	96 hour(s)	4.53 mg/l
	Pimephales promelas (LC50)	96 hour(s)	32.71 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	34.72 mg/l
	Pimephales promelas (LC50)	96 hour(s)	42.33 mg/l
	Poecilia reticulata (LC50)	96 hour(s)	57.68 mg/l
	Pimephales promelas (LC50)	96 hour(s)	93 mg/l

Products of degradation : These products are carbon oxides (CO, CO₂) and water.

Toxicity of the products of biodegradation : The products of biodegradation are as toxic as the original product.



Special remarks on the products of biodegradation : No additional remark.

Section 13. Disposal Considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	1203	Gasoline	3	II		Not available.
TDG Classification	1203	Gasoline (Hexane (Other Isomers), Toluene)	3	II		Not available.

Section 15. Regulatory Information

United States

U.S. Federal regulations : TSCA 4(a) final test rules: Hexane (Other Isomers); n-Hexane
 TSCA 8(a) PAIR: Tertiary Amyl Methyl Ether (TAME); n-Heptane; Pentane
 TSCA 8(b) inventory: Toluene; Hexane (Other Isomers); Xylene (o,m,p isomers); Octane (All Isomers); Methyl Tertiary Butyl Ether (MTBE); Ethanol; Tertiary Amyl Methyl Ether (TAME); 1,2,4-Trimethylbenzene; n-Heptane; Pentane; Cumene; Ethylbenzene; Benzene; n-Hexane; Cyclohexane; Trimethyl Benzene (Pseudocumene); Gasoline
 SARA 302/304/311/312 extremely hazardous substances: No products were found.
 SARA 302/304 emergency planning and notification: No products were found.
 SARA 302/304/311/312 hazardous chemicals: Toluene; Hexane (Other Isomers); Xylene (o,m,p isomers); Octane (All Isomers); Methyl Tertiary Butyl Ether (MTBE); Ethanol; 1,2,4-Trimethylbenzene; n-Heptane; Pentane; Cumene; Ethylbenzene; Benzene; n-Hexane; Cyclohexane
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Toluene: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Hexane (Other Isomers): Fire hazard, Immediate (Acute) Health Hazard; Xylene (o,m,p isomers): Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Octane (All Isomers): Fire hazard; Methyl Tertiary Butyl Ether (MTBE): Fire hazard, Immediate (Acute) Health Hazard; Ethanol: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; 1,2,4-Trimethylbenzene: Fire hazard, Delayed (Chronic) Health Hazard; n-Heptane: Fire hazard; Pentane: Fire hazard, Immediate (Acute) Health Hazard; Cumene: Fire hazard, Immediate (Acute) Health Hazard; Ethylbenzene: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Benzene: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; n-Hexane: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Cyclohexane: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Gasoline: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard
 Clean Water Act (CWA) 307: Toluene; Ethylbenzene; Benzene
 Clean Water Act (CWA) 311: Toluene; Xylene (o,m,p isomers); Ethylbenzene; Benzene; Cyclohexane
 Clean air act (CAA) 112 accidental release prevention: Pentane
 Clean air act (CAA) 112 regulated flammable substances: Pentane

Continued on next page

Clean air act (CAA) 112 regulated toxic substances: No products were found.

SARA 313

	<u>Product name</u>	<u>CAS number</u>	<u>Concentration</u>
Form R - Reporting requirements	: Toluene	108-88-3	0 - 30
	Xylene (o,m,p isomers)	1330-20-7	0 - 25
	Methyl Tertiary Butyl Ether (MTBE)	1634-04-4	0 - 16
	1,2,4-Trimethylbenzene	95-63-6	0 - 6
	Cumene	98-82-8	0 - 5
	Ethylbenzene	100-41-4	0 - 5
	Benzene	71-43-2	0 - 4.9
	n-Hexane	110-54-3	0 - 3
	Cyclohexane	110-82-7	0 - 3
	Supplier notification	: Toluene	108-88-3
Xylene (o,m,p isomers)		1330-20-7	0 - 25
Methyl Tertiary Butyl Ether (MTBE)		1634-04-4	0 - 16
1,2,4-Trimethylbenzene		95-63-6	0 - 6
Cumene		98-82-8	0 - 5
Ethylbenzene		100-41-4	0 - 5
Benzene		71-43-2	0 - 4.9
n-Hexane		110-54-3	0 - 3
Cyclohexane		110-82-7	0 - 3

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

: Connecticut carcinogen reporting list.: Benzene
 Connecticut hazardous material survey.: Toluene; Xylene (o,m,p isomers); Ethanol; Cumene; Ethylbenzene; Benzene; n-Hexane; Gasoline
 Illinois toxic substances disclosure to employee act: Toluene; Xylene (o,m,p isomers); Ethanol; Cumene; Ethylbenzene; Benzene; n-Hexane; Gasoline
 Rhode Island RTK hazardous substances: Toluene; Xylene (o,m,p isomers); Ethanol; Cumene; Ethylbenzene; Benzene; n-Hexane; Gasoline
 Pennsylvania RTK: Toluene: (environmental hazard, generic environmental hazard); Hexane (Other Isomers): (generic environmental hazard); Xylene (o,m,p isomers): (environmental hazard, generic environmental hazard); Octane (All Isomers): (generic environmental hazard); Methyl Tertiary Butyl Ether (MTBE): (environmental hazard, generic environmental hazard); Ethanol: (generic environmental hazard); 1,2,4-Trimethylbenzene: (environmental hazard, generic environmental hazard); n-Heptane: (generic environmental hazard); Pentane: (generic environmental hazard); Cumene: (environmental hazard, generic environmental hazard); Ethylbenzene: (environmental hazard, generic environmental hazard); Benzene: (special hazard, environmental hazard, generic environmental hazard); n-Hexane: (generic environmental hazard); Cyclohexane: (environmental hazard, generic environmental hazard); Trimethyl Benzene (Pseudocumene): (generic environmental hazard); Gasoline: (generic environmental hazard)
 Florida: Toluene; Xylene (o,m,p isomers); Ethanol; Cumene; Ethylbenzene; Benzene; n-Hexane; Gasoline
 Michigan critical material: Toluene; Xylene (o,m,p isomers); Cumene; Benzene
 Massachusetts RTK: Toluene; Hexane (Other Isomers); Xylene (o,m,p isomers); Octane (All Isomers); Methyl Tertiary Butyl Ether (MTBE); Ethanol; 1,2,4-Trimethylbenzene; n-Heptane; Pentane; Cumene; Ethylbenzene; Benzene; n-Hexane; Cyclohexane; Trimethyl Benzene (Pseudocumene); Gasoline
 New Jersey: Toluene; Xylene (o,m,p isomers); Octane (All Isomers); Methyl Tertiary Butyl Ether (MTBE); Ethanol; 1,2,4-Trimethylbenzene; n-Heptane; Pentane; Cumene; Ethylbenzene; Benzene; n-Hexane; Cyclohexane; Trimethyl Benzene (Pseudocumene); Gasoline
 Louisiana RTK reporting list: Gasoline

WARNING: This product contains chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm: Toluene; Benzene

WARNING: This product contains chemical(s) known to the state of California to cause reproductive harm (male): Benzene

California prop. 65 (no significant risk level): Benzene

California prop. 65 (acceptable daily intake level): Toluene; Benzene

WARNING: This product contains chemical(s) known to the state of California to cause birth defects or other reproductive harm.: Toluene; Benzene

WARNING: This product contains chemical(s) known to the state of California to cause cancer.: Benzene

Canada

WHMIS (Canada)

- : Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
- Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).
- Class D-2A: Material causing other toxic effects (VERY TOXIC).
- Class D-2B: Material causing other toxic effects (TOXIC).
- CEPA DSL: Toluene; Hexane (Other Isomers); Xylene (o,m,p isomers); Octane (All Isomers); Methyl Tertiary Butyl Ether (MTBE); Ethanol; Tertiary Amyl Methyl Ether (TAME); 1,2,4-Trimethylbenzene; n-Heptane; Pentane; Cumene; Ethylbenzene; Benzene; n-Hexane; Cyclohexane; Trimethyl Benzene (Pseudocumene); Gasoline

Section 16. Other Information


Label Requirements

- : CANCER HAZARD
- CONTAINS MATERIAL WHICH CAN CAUSE CANCER
- HIGHLY FLAMMABLE LIQUID AND VAPOR.
- HARMFUL IF SWALLOWED.
- CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS: BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, RESPIRATORY TRACT, SKIN, BONE MARROW, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.
- VAPOR MAY CAUSE FLASH FIRE.
- MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

Hazardous Material Information System (U.S.A.)

Health	1
Fire hazard	3
Physical Hazard	0
Personal protection	

National Fire Protection Association (U.S.A.)



- Date of printing** : 11/28/2005.
- Date of issue** : 11/28/2005.
- Date of previous issue** : No Previous Validation.
- Version** : 1

Disclaimer

THIS MATERIAL SAFETY DATA SHEET (“MSDS”) WAS PREPARED IN ACCORDANCE WITH 29 CFR 1910.1200 BY VALERO MARKETING & SUPPLY CO., (“VALERO”). VALERO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF PRODUCT USE BY OTHERS. THE INFORMATION, RECOMMENDATIONS, AND SUGGESTIONS PRESENTED IN THIS MSDS ARE BASED UPON TEST RESULTS AND DATA BELIEVED TO BE RELIABLE. THE END USER OF THE PRODUCT HAS THE RESPONSIBILITY FOR EVALUATING THE ADEQUACY OF THE DATA UNDER THE CONDITIONS OF USE, DETERMINING THE SAFETY, TOXICITY, AND SUITABILITY OF THE PRODUCT UNDER THESE CONDITIONS, AND OBTAINING ADDITIONAL OR CLARIFYING INFORMATION WHERE UNCERTAINTY EXISTS. NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, THE RESULTS TO BE

OBTAINED, OR THE SAFETY AND TOXICITY OF THE PRODUCT IN ANY SPECIFIC APPLICATION. FURTHERMORE, THE INFORMATION HEREIN IS NOT REPRESENTED AS ABSOLUTELY COMPLETE, SINCE IT IS NOT PRACTICABLE TO PROVIDE ALL THE SCIENTIFIC AND STUDY INFORMATION IN THE FORMAT OF THIS DOCUMENT, PLUS ADDITIONAL INFORMATION MAY BE NECESSARY UNDER EXCEPTIONAL CONDITIONS OF USE, OR BECAUSE OF APPLICABLE LAWS OR GOVERNMENT REGULATIONS.

Definitions of Material Safety Data Sheet Terminology

GOVERNMENT AGENCIES AND PRIVATE ASSOCIATIONS

ACGIH - American Conference of Governmental Industrial Hygienists, (private association)
DOT - United States Department of Transportation
EPA - United States Environmental Protection Agency
IARC - International Agency for Research on Cancer, (private association)
NFPA - National Fire Protection Association, (private association)
MSHA - Mine Safety and Health Administration, U.S. Department of Labor
NIOSH - National Institute of Occupational Safety and Health, U.S. Department of Health and Human Services
NTP - National Toxicology Program, (private association)
OSHA - Occupational Safety and Health Administration, U.S. Department of Labor
WHMIS - Workplace Hazardous Material Information System
CSA - Canadian Standards Association

HAZARD AND EXPOSURE INFORMATION

Acute Hazard - An adverse health effect which occurs rapidly as a result of short term exposure.
CAS # - American Chemical Society's Chemical Abstract service registry number which identifies the product and/or ingredients.
Ceiling - The concentration that should not be exceeded during any part of the working exposure
Chronic Hazard - An adverse health effect which generally occurs as a result of long term exposure or short term exposure with delayed health effects and is of long duration
Fire Hazard - A material that poses a physical hazard by being flammable, combustible, pyrophoric or an oxidizer as defined by 29 CFR 1910.1200
Hazard Class - DOT hazard classification
Hazardous Ingredients - Names of ingredients which have been identified as health hazards
IDLH - Immediately Dangerous to Life and Health, the airborne concentration below which a person can escape without respiratory protection and exposure up to 30 minutes, and not suffer debilitating or irreversible health effects. Established by NIOSH.
mg/m³ - Milligrams of contaminant per cubic meter of air, a mass to volume ratio
N/A - Not available or no relevant information found
NA - Not applicable
PEL - OSHA permissible exposure limit; an action level of one half this value may be applicable
ppm - Part per million (one volume of vapor or gas in one million volumes of air)
Pressure Hazard - A material that poses a physical hazard due to the potential of a sudden release of pressure such as explosive or a compressed gas as defined by 29 CFR 1910.1200
Reactive Hazard - A material that poses a physical hazard due to the potential to become unstable reactive, water reactive or that is an organic peroxide as defined by 29 CFR 1910.1200.
STEL - The ACGIH Short-Term Exposure Limit, a 15-minute Time-Weighted Average exposure which should not be exceeded at any time during a workday, even if the 8-hour TWA is less than the TLV.
TLV - ACGIH Threshold Limit Value, represented herein as an 8-hour TWA concentration.
8-hour TWA - The time weighted average concentration for a normal 8-hour workday and a 40-hour workweek, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect.
LD₅₀ - Single dose of a substance that, when administered by a defined route in an animal assay, is expected to cause the death of 50% of the defined animal population.
LC₅₀ - The concentration of a substance in air that, when administered by means of inhalation over a specified length of time in an animal assay, is expected to cause the death of 50% of a defined animal population.